

WORLD WIND™ HAIR DRYER



For lighter applications, the WorldWind™ hair dryer is a wall-mounted unit that isolates electrical components from accidental water contact. It automatically activates when hand piece is removed from base and deactivates when replaced. The hose and hand piece are insulated to prevent heat build-up. Recommended for hotels, hospitals, nursing homes and residential usage. Available in white.

Features

Delivers 1,000 Watts of power

Regulates airflow with convenient dial


15-minute electronic timer

Easy installation

Warranty

One year limited

WORLD WIND™ SPECIFICATIONS

World Wind™ models HD3 & HD5 shall be manufactured by or for World Dryer® to include splash proof enclosure. Hair dryers shall include a flexible hose permanently attached to direct airflow. Unit shall be equipped with variable speed airflow dial, and shall deliver 45 CFM of air volume at maximum rated voltage. Dryer shall be equipped with plug with ALCI protection. Unit to be listed under reexamination service of Underwriters Laboratories. 

SPECIFIER'S APPROVAL

Job _____	Date _____
Model Number _____	Quantity _____
Variations _____	
Customer/Wholesaler _____	
Contractor _____	
Architect/ Engineer _____	

Electronic specifications available online: www.worlddryer.com/specs



MODEL NUMBERS

MODEL NUMBER	ELECTRICAL			
	Volts	Amps	Watts	Freq
HD3	110-120	9.1	1000	60 Hz
HD5*	220	4.5	1000	50 Hz

* Export Models only

MEASUREMENTS

UNIT MEASUREMENTS	SHIPPING WEIGHT	SHIPPING DIMENSIONS
8" W x 23-1/2" H x 4" D	6 lbs	19" L x 8-1/2" W x 4-3/4" H

MOUNTING HEIGHTS

Surface	
Men	58" (147cm)
Women	58" (147cm)
Children ages 3-7	58" (147cm)
Children ages 8-10	58" (147cm)
Children ages 11-13	58" (147cm)
Children ages 14-17	58" (147cm)
Disabled	38" (86cm)

Measured from floor to the bottom of the unit